

U.S. Application No. 10/016,719 – Filed: December 10, 2001  
Amendment Dated: August 7, 2003  
Reply to Office Action Dated: April 24, 2003

**Amendments to the Abstract:**

Please replace the paragraph beginning at page 16, line 2, with the following rewritten paragraph:

Q8 A device for balancing ~~of a radial threaded spindle~~ eccentricity of a spindle drive (1) to avoid blocking of the spindle drive during lifting movement of a platform (2), in which the platform is mounted on several axiparallel spindles (G1; G2; G3; G4) by bearing devices (L1; L2; L3; L4) arranged on it and can be lifted together with the bearing devices axially along the spindle. The spindle drive (1) has at least three axiparallel, rotatable threaded spindles (G1; G2; G3; G4) with bearing device (L1; L2; L3; L4) ~~with different or the same bearing clearance (F1; F2)~~ in a polygonal arrangement; low-friction bearing devices (L1; L2; L3; L4) with radial bearing clearance (F1; F2) are arranged to balance the radial eccentricity of the rotating threaded spindles so that a relative radial movement of the rotating spindles to platform (2) is possible with limited force expenditure; ~~and the bearing devices (L1; L2; L3; L4) each have an annular ball bearing (3) arranged concentrically around the spindles (G1; G2; G3; G4).~~